

Security considerations

>>> Announcements:

- ◆ Pls check the appearance and the unit functions before install the unit.
- ◆ Don't shorten or extended the GPS antenna, it will lead to the antenna problem.
- ◆ Don't make the GPS antenna winding the steering wheel and shift lever, it will be dangerous.

>>> Warm prompt

1. Don't use strong chemicals, cleaning agents, strong detergent to washing the machine.
2. Please use a clean soft fabric to wipe the screen, don't use ordinary fabric.
3. Please use the touch screen pen to operation unit, please don't use other sharp objects, or it will damage to the screen.
4. Please don't self-service, maintenance or install the unit, in case of the power is on, don't install or repair the unit. It is very dangerous if the person who did not receive the electronic equipment or vehicle installation training or lack of experienced personnel to install and repair the unit.
5. Please protect the original display when the staff dismounting the original CD and keep the original CD, try to use the original screw.
6. Navigation and rearview camera only do auxiliary function, it can't replace your attention and judgment.
7. When the customer choose the digital TV, our unit could realized the digital TV touch.

The publicity material only for reference, we don't make the further notice if the information have any changes, our company has the final explanation right!

Installation Instruction and Things to Note

BMW 2013 Mini



Installation Procedure



◆ 1. Original bmw mini (2013)



◆ 2. Original center console



◆ 3. Plug down the locking lever of the steering wheel ,pull out the steering wheel and remove the screws beside the revolution meter.



◆ 4. Pry up the original car silver shield on the left



◆ 5. Remove the four screw, then remove the circle



◆ 6. Remove the big circle and Warning lamp's flat cable, noted the flat cable's clip



◆ 7. Take out the two sides panels of the dashboard and pay attention on the snap joint in the two side

Installation Procedure



◆ 8. Take out the screw in the side panel



◆ 9. Take out the screw in the long paddle, and pay attention to adjust the gear to D. Then gently pick up the back.



◆ 10. Take out the dashboard and pay attention to the wires.



◆ 11. Take out the original CD screws

◆ 12. Teardown the original car CD tail line and on line, cost of replacement products. Plug machine after the entire car key boot, machine no problem original back again



◆ 13. Installation photo